

CIMVANTAGE® 31-48

Cutting fluid for medium duty applications











Description

Cimvantage 31-48 is a general purpose, water miscible, micro-fine emulsion with excellent washing action and ferrous corrosion protection.

Application

Cimvantage 31-48 is an all-round cutting fluid recommended for medium duty grinding and machining of all ferrous metals. It is designed for a wide water hardness range (10-25° dH).

Features and benefits

- · Clean and mild product with excellent washing action.
- · Economical due to low top-up.
- · Suitable for a wide range of operations.
- · Excellent ferrous corrosion properties.
- · Good foam control in the indicated water hardness range.
- · Easy to mix with water.



Methods of application

Cimvantage 31-48 is easy to mix, normal stirring only. For automatic mixing, the use of the Cimcool® Mix Master or Cimcool Mix Master S is recommended. Typical starting water temperature conditions should be 5 - 25°C.

Recommended starting concentration

Grinding & machining	5 - 12 %

Mix Master S

Concentration** can easily be obtained by setting the regulator to the correct number.

** The concentration may vary depending on local conditions. It is therefore always advised to check using the refractometer or TA Kit.

Concentration analysis

For concentration analysis, use one of the below given methods or an appropriate laboratory procedure available from your local stockist.

Refractometer factor:	2.2
-----------------------	-----

If the refractometer is used, the resultant reading multiplied by a factor of 2.2 will only be relevant when applied to a fresh mix.

Cimcool TA kit			Use 2 ml. mix				*: next syringe			
%	1	2	3	4	5	6	7	8	9	10
Reading	0.82	0.67	0.51	0.36	0.20	0.04	*.89	*.73	*.58	*.42

Handling and storage

Protect from freezing, direct sun and store between 5 - 35°C.

Packaging type

200 and 1000 litre.

Safety Data Sheet

The Safety Data Sheet should be consulted for specific information and information on Health, Safety and Environment when handling this product.





