



Description

Milpro GEAR CLP 68 is a high-grade industrial gear oil, based on mineral oil, under addition of lead-free EP-additives.

Application

To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

Features and benefits

- A very good resistance towards high pressures and hock loads
- A good resistance against high temperatures
- Good rust- and corrosion preventing properties
- An excellent prevention from wear
- A very good activity against foaming
- A low pour point

Performance Level

DIN 51517, 3

FZG 12

US Steel 224

Typical characteristics

	Units	Grade
Density at 15°	C Kg/L	0,881
Viscosity at 40° C	mm ² /s	68,00
Viscosity at 100° C	mm ² /s	8,60
Viscosity Index		97
Flash point COC	° C	220
Pour point	° C	-20

Above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Handling and storage

All packages should be stored under cover. Outside drums should be in a horizontal position. Protect against freezing and temperature above 40°C.

Packaging type

5, 25, 200 and 1.000 litres and bulk.

Safety Data Sheet

The Safety Data Sheet should be consulted for specific information and information on Health, Safety and Environment when handling this product.



Cimcool Industrial Products
Schiedamsedijk 20
3134 KK Vlaardingen
The Netherlands
Tel: +31 (0)10-4600660
cimcool.eu@duboischemicals.com
www.cimcool.com

