

CIMPERIAL® 31-281FF

Automotive range

Formaldehyde releasing biocides free cutting and grinding fluid for heavy-duty applications



PRODUCT INFORMATION FLYER

Description

Cimperial 31-281FF is an excellent all-round emulsion suitable for many heavy-duty machining operations including grinding. Cimperial 31-281FF is free from formaldehyde releasing biocides.

Application

Cimperial 31-281FF is suitable for a great number of metals ranging from aluminium to steel and stainless steel. The potential aluminium staining has been minimised making Cimperial 31-281FF very suitable for the aluminium types used in the automotive supplier industry.

Cimperial 31-281FF is especially developed for use in soft water (5 to 15°dH in starting water). In case of harder water Cimperial 31-278FF is advised.

Features and benefits

Cimperial 31-281FF is an excellent multipurpose and hassle-free emulsion. It provides a high quality finish and excellent stability. This stability ensures a long fluid life, which makes Cimperial 31-281FF a very cost-effective product.

Cimperial 31-281FF is a mild and formaldehyde releasing biocide free product. It will keep grinding wheels open and maintains machine cleanliness.

Cimperial 31-281FF notably improves production. Effective lubricants reduce the amount of heat generated in the cutting zone permitting higher speeds and feeds, thereby increasing production while maintaining or improving overall part quality.

Methods of application

Cimperial 31-281 is easy to mix, normal stirring only. For automatic mixing, the use of the Cimcool® Mix Master or Cimcool Mix Master S is recommended. Typical starting water temperature conditions should be 5 - 25°C.

Recommended starting concentration

| | |
|-----------|----------|
| Grinding | 5 - 8 % |
| Machining | 5 - 10 % |

Mix Master S

Concentration** can easily be obtained by setting the regulator to the correct number.

** The concentration may vary depending on local conditions. It is therefore always advised to check using the refractometer or TA Kit.

Concentration analysis

For concentration analysis, use one of the below given methods or an appropriate laboratory procedure available from your local stockist.

| | |
|-----------------------|-----|
| Refractometer factor: | 1.1 |
|-----------------------|-----|

If the refractometer is used, the resultant reading multiplied by a factor of 1.1 will only be relevant when applied to a fresh mix.

| Cimcool TA kit | Use 2 ml. mix | | | | | | | | *: next syringe | |
|----------------|---------------|------|------|------|------|------|------|------|-----------------|------|
| % | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Reading | 0.86 | 0.75 | 0.64 | 0.53 | 0.42 | 0.31 | 0.19 | 0.08 | *.97 | *.86 |

Handling and storage

Protect from freezing, direct sun and store between 5 - 35°C.

Packaging type

200 and 1.000 litre.

Safety Data Sheet

The Safety Data Sheet should be consulted for specific information and information on Health, Safety and Environment when handling this product.



Cimcool Industrial Products
Schiedamsedijk 20
3134 KK Vlaardingen
The Netherlands
Tel: (0)10-4600660
cimcool.eu@duboischemicals.com
www.cimcool.com

