

CIMSTAR® 126FF

Cutting and grinding fluid for medium duty applications without formaldehyde releasing biocides











Description

Cimstar 126FF is a water miscible, semi-synthetic cutting fluid concentrate. Cimstar 126FF is free from formaldehyde releasing biocides.

Application

Cimstar 126FF is a general-purpose cutting and grinding fluid for use in single machines and central systems on all ferrous and most non-ferrous metals.

Features and benefits

- · Free from Formaldehyde Releasing Agents (FRA).
- Long fluid life due to the special product composition, ideal for central systems.
- · Effective lubrication and cooling action.
- · No increased disposal costs chlorine free.
- · Provides long term rust control.
- Clean, pleasant to use low misting, good foam control.
- Can be used in water up to 10 20° dH.



Methods of application

Cimstar 126FF is easy to mix, normal stirring only. For automatic mixing, the use of the Cimcool Mix Master S is recommended. Typical starting water temperature conditions should be 5 - 25°.

Recommended starting concentration

| Grinding | 4 - 6 % |
|-----------|---------|
| Machining | 6 - 8 % |

Mix Master S

Concentration** can easily be obtained by setting the regulator to the correct number.

** The concentration may vary depending on local conditions. It is therefore always advised to check using the refractometer.

Concentration analysis

For concentration analysis, use the below given method or an appropriate laboratory procedure available from your local stockist.

Refractometer factor: 3.3

If the refractometer is used, the resultant reading multiplied by a factor of 3.3 will only be relevant when applied to a fresh mix.

| Cimcool TA kit | | | Use 2 ml. mix | | | | | *: next syringe | | |
|----------------|------|------|---------------|------|------|------|------|-----------------|------|------|
| % | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Reading | 0.85 | 0.71 | 0.58 | 0.44 | 0.30 | 0.17 | 0.03 | *.89 | *.76 | *.62 |

Handling and storage

Protect from freezing, direct sun and store between 5 - 35°C.

Packaging type

200 and 1.000 litre.

Safety Data Sheet

The Safety Data Sheet should be consulted for specific information and information on Health, Safety and Environment when handling this product.





