

Spindle oil / Hydraulic oil



## Description

Mipro Spindle 10 is based on low viscosity hydrotreated base oil with very good low temperature properties.

## Application

Milpro Spindle 10 is designed for all types spindle bearings including high speed spindles. It provides excellent oxydation stability and rust protection.

## Features

- Excellent oxydation properties
- Rust & corrosion protection
- Easily applied by low temperature
- Low staining properties

## Performance level

- DIN 51502 classification - HL
- ISO 6743/4 - Hydraulic oil HL
- ISO 6743/2 - Spindle oil type FC

## Typical characteristics

	Units	Grade
Color ASTM D1500	-	0,5
Density at 15°	Kg/L	889
Viscosity at 40° C	mm <sup>2</sup> /s	9,5
Viscosity at 100° C	mm <sup>2</sup> /s	2,2
Flash point PMCC	° C	> 140
Pour point	° C	< -45

Above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Handling and storage

All packages should be stored under cover. Outside drums should be in a horizontal position. Protect against freezing and temperature above 40° C.

## Packaging type

5, 25, 200 and 1.000 litres and bulk.

## Safety Data Sheet

The Safety Data Sheet should be consulted for specific information and information on Health, Safety and Environment when handling this product.



**Cimcool Industrial Products**  
Schiedamsedijk 20  
3134 KK Vlaardingen  
The Netherlands  
Tel: +31 (0)10-4600660  
cimcool.eu@duboischemicals.com  
[www.cimcool.com](http://www.cimcool.com)

